



BALAD BAMBOO

LIGHTING

BALAD

365100 - SET OF 3 LAMPS BAMBOO H.12 CM

DESIGN BY TRISTAN LOHNER

DOMESTIC PROFESSIONAL INTENSIVE



Polyethylene diffuser

Bamboo frame

ABS base

Technology : integrated LED - Luminous flux : 20 lm

Switch type : push button

Function of the switch : change the light temperature & brightness
(short click, 1 s), OFF (long click, 3 s)

Lighting mood :

Position 1 cool white (6000°K) 100% brightness

Position 2 neutral white (4000°K) 100% brightness

Position 3 candle-style warm white (2300°K) flickering

Type of power supply : battery - Battery life : Min. (100%) 10 h - Max. 13 h


Battery use cycles : 500 cycles

Recharge time : 4h - Type of recharge : USB, cable (supplied) 1,5m

Bypass to prevent battery damage during wired use

0.25 A - 5 V - 0.3 W - IP44 (ingress protection) | IK 10 (impact resistance) | CE | FCC | UKCA

Powered by Smart & Green



0.13 kg

365200 - LAMP BAMBOO H.25 CM

DESIGN BY TRISTAN LOHNER

DOMESTIC PROFESSIONAL INTENSIVE



Polyethylene diffuser

Bamboo frame

ABS base

Technology : integrated LED - Luminous flux : 40 lm

Switch type : push button

Function of the switch : change the light temperature & brightness
(short click, 1 s), OFF (long click, 3 s)

Lighting mood :

Position 1 cool white (6000°K) 100% brightness

Position 2 neutral white (4000°K) 100% brightness

Position 3 neutral white (4000°K) 50% brightness

Position 4 candle-style warm white (2300°K) flickering

Type of power supply : battery - Battery life : Min. (100%) 7 h - Max. 14 h


Battery use cycles : 300 cycles

Recharge time : 5h - Type of recharge : USB, cable (supplied) 2m

Bypass to prevent battery damage during wired use

0.5 A - 5 V - 0.5 W - IP44 (ingress protection) | IK 10 (impact resistance) | CE | FCC | UKCA

Powered by Smart & Green



0.47 kg

BALAD

365300 - LAMP BAMBOO H.38 CM

DESIGN BY TRISTAN LOHNER

DOMESTIC | PROFESSIONAL | INTENSIVE



Polyethylene diffuser

Bamboo frame

ABS base

Technology : integrated LED - Luminous flux : 150 lm

Switch type : push button

Function of the switch : change the light temperature & brightness
(short click, 1 s), OFF (long click, 3 s)

Lighting mood :

Position 1 cool white (6000°K) 100% brightness

Position 2 cool white (6000°K) 50% brightness

Position 3 neutral white (4000°K) 100% brightness

Position 4 neutral white (4000°K) 50% brightness

Position 5 candle-style warm white (2300°K) flickering

Type of power supply : battery - Battery life : Min. (100%) 9 h - Max. 16 h

Battery use cycles : 300 cycles

Recharge time : 7h - Type of recharge : USB, cable (supplied) 2m

Bypass to prevent battery damage during wired use

2 A - 5 V - 2.5 W - IP44 (ingress protection) | IK 10 (impact resistance) | CE | FCC | UKCA

Energy rating : E

Powered by Smart & Green



1.08 kg



BALAD



BALAD